

2110

5½-Digit Dual-Display Digital Multimeter



- High accuracy, high speed for general purpose measurements
- 15 measurement functions, including capacitance and thermocouple measurements
- Dual-line display allows concurrent measurements
- TMC-compliant USB 2.0 interface for use with SCPI test commands
- GPIB option for use in system applications
- Includes PC software utilities for graphing and data sharing in both Microsoft® Word and Excel
- Rugged construction for durability in bench/portable applications
- Includes all accessories, such as start-up software, USB cable, power cable, and safety test leads
- CE compliant and cUL^{US} listed

APPLICATIONS

Built for Production Testing

The Model 2110 Digital Multimeter is ideal for applications in manual, semi-automatic, and automatic testing of low-cost electronic devices, circuits, modules, electrical components, and semiconductor components. Key features include:

- **Speed: up to 50,000 readings per second**
- **Control: GPIB (optional) and USB interfaces, accepting SCPI (IEEE-488.2) commands**
- **External BNC trigger lines**
- **NIST traceability (with included calibration certificate)**

Built for General Purpose Uses

The Model 2110 Digital Multimeter is also ideal for bench uses such as research, development, service, calibration, and teaching. Bench-oriented features include:

- **Accuracy: 0.012% basic DCV accuracy**
- **Easy-to-operate panel**
- **Easy waveform plotting and data collection with KI-Tool and KI-Link**
- **Store up to 2000 readings**

The Model 2110 5½-Digit Dual-Display Digital Multimeter combines a compelling price with a comprehensive set of capabilities, superior measurement accuracy, and high speed for a broad range of applications. It features 15 measurement functions and 7 math functions and has dual-line display capability, which allows it to display two different measurements concurrently. The Model 2110 is an unbeatable value for production, R&D, and test engineers, scientists, and students making a wide variety of measurements in portable, bench, and system applications.

High Accuracy, Abundant Capabilities, Low Cost

The Model 2110 provides precision and a rich set of capabilities at a value price. It has 0.012% one-year basic DC voltage accuracy and 0.020% one-year basic resistance accuracy up to the 100kΩ range.

The Model 2110 provides a wide number of measurement ranges and functions:

- DC voltage: 0.1V, 1V, 10V, 100V, and 1000V
- AC voltage: 0.1V, 1V, 10V, 100V, and 750V
- DC current: 10mA, 100mA, 1A, 3A, and 10A
- AC current: 1A, 3A, and 10A
- Two- and four-wire resistance: 100Ω, 1kΩ, 10kΩ, 100kΩ, 1MΩ, 10MΩ, and 100MΩ
- Frequency: From 10Hz to 300kHz
- Capacitance measurement: 1nF, 10nF, 100nF, 1μF, 10μF, 100μF
- Thermocouple measurement: J-, R-, S-, T-, E-, N-, B-, C-, and K-type thermocouples
- Temperature (RTD and NTC Thermistor) measurements
- Diode measurement
- Continuity test
- Programmable A-D converter and filter settings for signal to noise optimization. Additionally, seven mathematical operations can be performed on measurement readings: percentage, average, min/max, NULL, limits, mX+b, dB, and dBm testing.

Speed

At 5½ digits, the Model 2110 delivers up to 200 readings/s via the USB remote interface. At the fast 4½-digit setting, it reads up to 50,000 readings/s and up to 30,000 readings/s into the buffer, making it ideal for production and monitoring applications in which speed is critical.

1.888.KEITHLEY (U.S. only)

www.keithley.com

A Greater Measure of Confidence

KEITHLEY

A Tektronix Company

Low-cost 5½-digit DMM for system, bench, or portable applications

DIGITAL MULTIMETERS & SYSTEMS

2110

5½-Digit Dual-Display Digital Multimeter

Ordering Information

- 2110-100: 5½-digit USB Digital Multimeter (100V)
- 2110-120: 5½-digit USB Digital Multimeter (120V)
- 2110-220: 5½-digit USB Digital Multimeter (220V)
- 2110-240: 5½-digit USB Digital Multimeter (240V)
- 2110-GPIB-100: 5½-digit USB and GPIB Digital Multimeter (100V)
- 2110-GPIB-120: 5½-digit USB and GPIB Digital Multimeter (120V)
- 2110-GPIB-220: 5½-digit USB and GPIB Digital Multimeter (220V)
- 2110-GPIB-240: 5½-digit USB and GPIB Digital Multimeter (240V)

Accessories Supplied

Reference Manual on CD, Specifications, LabVIEW® Driver, Keithley I/O Layer, USB Cable, Power Cable, Safety Test Leads, KI-Tool, and KI-Link Add-in (both Microsoft Word and Excel versions), Calibration Certificate



All accessories, such as start-up software, USB cable, power cable, and safety test leads, are included with the Model 2110.

Simplicity

The Model 2110 is operational and intuitive to use right out of the box. The functions on the front panel are user friendly and easy to read. Its KI-Tool and KI-Link software allow users to quickly control the instrument over GPIB (if equipped) or USB, record measurements, and display time-series plots of the data. Its LabVIEW® and IVI drivers give more-advanced customers even more control over the instrument. Both the TMC-compliant USB remote interface and the GPIB interface allow easy re-use of existing SCPI programs.

Startup Software, PC Utilities Included

The KI-Tool application provides charting and graphing capabilities without programming to simplify setup, checkout, and basic measurement applications requiring graphical data representation. Scale, offset, and level can be adjusted to fine-tune images for visual evaluation of signal and noise elements over time. It also includes tabular data and SCPI command prompt windows for maximum flexibility. Data sets can also be saved to disk files.

The Microsoft Excel Add-In utility is also included and provides quick data import into a standard Microsoft Excel spreadsheet, including selectable graphing, instrument settings, and number of data points collected. Data can then be analyzed through standard or optional Microsoft Excel functions,

including graphical, statistical, and trend charting. A version supporting Microsoft Word is also included for direct data import into reports.

LabView, IVI-C, and IVI-COM drivers are also supplied to allow for increased flexibility in integrating the Model 2110 into new and existing systems and test routines.



KI-Tool simplifies basic measurement applications through every setup and graphical data representation.

1.888.KEITHLEY (U.S. only)

www.keithley.com

A Greater Measure of Confidence

KEITHLEY
A Tektronix Company

Specifications

DC CHARACTERISTICS

DC VOLTAGE			Accuracy ¹	Temperature Coefficient
Range	Resolution	Input Resistance	±(% of reading + % of range)	0°–18°C & 28°–40°C
100.000 mV	1 µV	10 MΩ	0.012 + 0.004	0.001 + 0.0005
1.00000 V	10 µV		0.012 + 0.001	0.0009 + 0.0005
10.0000 V	0.1 mV		0.012 + 0.002	0.0012 + 0.0005
100.000 V	1 mV		0.012 + 0.002	0.0012 + 0.0005
1000.00 V	10 mV		0.02 + 0.003	0.002 + 0.0015

DCI (DC CURRENT)			Accuracy ¹	Temperature Coefficient
Range	Resolution	Shunt Resistance	±(% of reading + % of range)	0°–18°C & 28°–40°C
10.0000 mA	0.1 µA	5.1 Ω	0.05 + 0.020	0.005 + 0.002
100.000 mA	1 µA	5.1 Ω	0.05 + 0.010	0.005 + 0.001
1.00000 A	10 µA	0.1 Ω	0.150 + 0.020	0.008 + 0.001
3.0000 A	100 µA	0.1 Ω	0.200 + 0.030	0.008 + 0.001
10.0000 A	100 µA	5 mΩ	0.250 + 0.050	0.008 + 0.001

RESISTANCE ²			Accuracy ¹	Temperature Coefficient
Range	Resolution	Test Current	±(% of reading + % of range)	0°–18°C & 28°–40°C
100.000 Ω	1 mΩ	1 mA	0.020 + 0.020	0.003 + 0.0005
1.00000 kΩ	10 mΩ	1 mA	0.020 + 0.003	0.003 + 0.0005
10.0000 kΩ	100 mΩ	100 µA	0.020 + 0.002	0.003 + 0.0005
100.000 kΩ	1 Ω	10 µA	0.020 + 0.002	0.003 + 0.0005
1.00000 MΩ	10 Ω	1 µA	0.030 + 0.004	0.005 + 0.0005
10.0000 MΩ	100 Ω	0.1 µA	0.200 + 0.004	0.05 + 0.0005
100.000 MΩ	1 kΩ	0.1 µA	2.000 + 0.005	0.5 + 0.0005

DIODE TEST			Accuracy ¹	Temperature Coefficient
Range	Resolution	Test Current	±(% of reading + % of range)	0°–18°C & 28°–40°C
1.0000V	10 µV	1 mA	0.020 + 0.030	0.002 + 0.0005

CONTINUITY			Accuracy ¹	Temperature Coefficient
Range	Resolution	Test Current	±(% of reading + % of range)	0°–18°C & 28°–40°C
1000Ω	10 mΩ	1 mA	0.020 + 0.020	0.002 + 0.0005

- Specifications valid after two hour warm-up.
 - ADC set for continuous trigger operation.
 - Input bias current <30pA at 25°C.
 - Measurement rate set to 10 PLC.
- Specifications for 4W ohms mode. For 2W ohms, use zero null or subtract lead resistance from displayed reading.
 - Maximum lead resistance 10% of range per lead for 100Ω and 1kΩ ranges; add 1kΩ per lead for all other ranges.

MEASUREMENT NOISE REJECTION DC (60Hz/50Hz) at 5.5 DIGITS

CMRR: 120dB for 1kΩ unbalance in LO lead.

NMRR: 60dB for line frequency ±0.1%.

TEMPERATURE (THERMOCOUPLE) CHARACTERISTICS		
Thermocouple Type	Range	Accuracy ¹ ±°C 1 Year, exclusive of lead accuracy
B	600 to 1800°C	1.5
C	0 to 2300°C	1.5
E	–250 to 1000°C	1.5
J	–200 to 1200°C	1.0
K	–200 to 1350°C	1.0
N	–200 to 1300°C	1.0
R	0 to 1750°C	1.5
S	0 to 1750°C	1.5
T	–250 to 400°C	1.5

- Specifications valid after two hour warm-up.
 - ADC set for continuous trigger operation.
- RTD AND NTC THERMISTOR MEASUREMENTS: Accuracy ±0.8°C, 1 year, exclusive of lead accuracy. PT100, D100, F100, PT385, PT3916, SPRTD (R-Zero, A4, B4, Ax, Bx, Cx, and Dx), NTCT (A, B, and C), and user-definable RTD.

CAPACITANCE CHARACTERISTICS		
Range	Test Current	Accuracy ¹ ±(% of reading + % of range) 1 Year, 23° ±5°C
1.000 nF	10 µA	2.0 + 0.80
10.00 nF	10 µA	1.0 + 0.50
100.0 nF	100 µA	1.0 + 0.50
1.000 µF	100 µA	1.0 + 0.50
10.00 µF	100 µA	1.0 + 0.50
100.0 µF	1 mA	1.0 + 0.50

- Specifications valid after two hour warm-up.
 - ADC set for continuous trigger operation.
 - Null enabled.

ACCESSORIES AVAILABLE

4299-3	Single Rack Mount Kit
4299-4	Dual Rack Mount Kit
4299-7	Fixed Rack Mount Kit
5805	Kelvin Probes, 0.9m (3ft)
5805-12	Kelvin Probes, 3.6m (12ft)
5808	Low Cost, Single Pin, Kelvin Probes
5809	Low Cost, Kelvin Clip Lead Set
6517-TP	Thermocouple Bead Probe (K-Type)
7007-1	Shielded GPIB Cable, 1m (3.3 ft)
7007-2	Shielded GPIB Cable, 2m (6.6 ft)
8605	High Performance Modular Test Leads
8606	High Performance Modular Probe Kit
8680	RTD Probe Adapter
8681	Low Cost RTD

SERVICES AVAILABLE

2110-3Y-EW	1 Year Factory Warranty extended to 3 years from date of shipment
2110-5Y-EW	1 Year Factory Warranty extended to 5 years from date of shipment
C/2110-3Y-DATA	3 (Z-540-1 compliant) calibrations within 3 years of purchase for Model 2110
C/2110-5Y-DATA	5 (Z-540-1 compliant) calibrations within 5 years of purchase for Model 2110
C/2110-3Y-ISO	3 (ISO-17025 accredited) calibrations within 3 years of purchase for Model 2110
C/2110-5Y-ISO	5 (ISO-17025 accredited) calibrations within 5 years of purchase for Model 2110

1.888.KEITHLEY (U.S. only)

www.keithley.com

KEITHLEY

A Greater Measure of Confidence

A Tektronix Company

AC CHARACTERISTICS

FREQUENCY AND PERIOD		Accuracy ¹	Temperature Coefficient
Range	Frequency (Hz)	±(% of reading + % of range) 1 Year, 23° ±5°C	0°–18°C & 28°–40°C
100.000 mV to 750.000 V ²	10–40 40–300k	0.03 0.02	0.002 0.002

ACV (AC TRMS VOLTAGE)			Accuracy ¹	Temperature Coefficient
Range	Resolution	Frequency	±(% of reading + % of range) 1 Year, 23° ±5°C	0°–18°C & 28°–40°C
100.000 mV to 750.000 V ²	1 μV to 10 mV	10 Hz–20 kHz 20 kHz–50 kHz 50 kHz–100 kHz 100 kHz–300 kHz	0.12 + 0.05 0.25 + 0.05 0.65 + 0.08 5.00 + 0.50	0.01 + 0.01 0.02 + 0.02 0.04 + 0.02 0.2 + 0.02

ACI (AC TRMS CURRENT)			Accuracy ¹	Temperature Coefficient
Range	Resolution	Frequency	±(% of reading + % of range) 1 Year, 23° ±5°C	0°–18°C & 28°–40°C
1.0000 A to 3.00000 A	10 μA to 100 μA	10 Hz–900 Hz 900 Hz–5 kHz	0.30 + 0.06 1.50 + 0.15	0.02 + 0.01 0.02 + 0.01
10.0000 A	100 μA	10 Hz–900 Hz 900 Hz–5 kHz	0.50 + 0.12 2.50 + 0.20	0.02 + 0.01 0.02 + 0.01

- Specifications valid after two hour warm-up.
 - Slow AC filter (3Hz bandwidth).
 - Pure sine wave input greater than 5% of range.
- 750VAC range is limited to 100kHz.

GENERAL

INPUT BIAS CURRENT: <30pA at 25°C.
 INPUT PROTECTION: 1000V all ranges (2W input).
 AC CMRR: 70dB (for 1kΩ unbalance LO lead).
 POWER SUPPLY: 100V/120V/220V/240V.
 POWER LINE FREQUENCY: 50/60Hz auto detected.
 POWER CONSUMPTION: 25VA max.
 DIGITAL I/O INTERFACE: USB-compatible Type B connection, GPIB (option).
 ENVIRONMENT: For indoor use only.
 OPERATING TEMPERATURE: 0° to 40°C.
 OPERATING HUMIDITY: Maximum relative humidity 80% for temperature up to 31°C.
 STORAGE TEMPERATURE: –40° to 70°C.
 OPERATING ALTITUDE UP TO 2000 M ABOVE SEA LEVEL.
 BENCH DIMENSIONS (WITH HANDLES AND BUMPERS): 107 mm high × 252.8 mm wide × 305 mm deep (3.49 in. × 9.95 in. × 12.00 in.).
 WEIGHT: 2.23 kg (4.92 lbs.).
 SAFETY: Conforms to European Union Low Voltage Directive, EN61010-1. Measurement Cat I 1000V and CAT II 600V.
 EMC: Conforms to European Union Directive 89/336/EEC, EN61326-1.
 WARRANTY: One year.



Model 2110 rear panel.

Specifications are subject to change without notice. All Keithley trademarks and trade names are the property of Keithley Instruments, Inc. All other trademarks and trade names are the property of their respective companies.

KEITHLEY

A Tektronix Company

A Greater Measure of Confidence

KEITHLEY INSTRUMENTS, INC. ■ 28775 AURORA RD. ■ CLEVELAND, OH 44139-1891 ■ 440-248-0400 ■ Fax: 440-248-6168 ■ 1-888-KEITHLEY ■ www.keithley.com

BELGIUM

Sint-Pieters-Leeuw
 Ph: 02-3630040
 Fax: 02-3630064
 info@keithley.nl
 www.keithley.nl

CHINA

Beijing
 Ph: 86-10-8447-5556
 Fax: 86-10-8225-5018
 china@keithley.com
 www.keithley.com.cn

FRANCE

Les Ulis
 Ph: 01-69868360
 Fax: 01-69868361
 info@keithley.fr
 www.keithley.fr

GERMANY

Germering
 Ph: 089-84930740
 Fax: 089-84930734
 info@keithley.de
 www.keithley.de

INDIA

Bangalore
 Ph: 080-30792600
 Fax: 080-30792688
 support_india@keithley.com
 www.keithley.in

ITALY

Peschiera Borromeo (Mi)
 Ph: 02-5538421
 Fax: 02-55384228
 info@keithley.it
 www.keithley.it

JAPAN

Tokyo
 Ph: 81-3-6714-3070
 Fax: 81-3-6714-3080
 info.jp@keithley.com
 www.keithley.jp

KOREA

Seoul
 Ph: 82-2-574-7778
 Fax: 82-2-574-7838
 keithley@keithley.co.kr
 www.keithley.co.kr

MALAYSIA

Penang
 Ph: 60-4-643-9679
 Fax: 60-4-643-3794
 sea@keithley.com
 www.keithley.com

NETHERLANDS

Son
 Ph: 040-2675502
 Fax: 040-2675509
 info@keithley.nl
 www.keithley.nl

SINGAPORE

Singapore
 Ph: 65-6747-9077
 Fax: 65-6747-2991
 sea@keithley.com
 www.keithley.com.sg

TAIWAN

Hsinchu
 Ph: 886-3-572-9077
 Fax: 886-3-572-9031
 info_tw@keithley.com
 www.keithley.com.tw

UNITED KINGDOM

Bracknell
 Ph: 044-1344-392450
 Fax: 044-1344-392457
 info@keithley.co.uk
 www.keithley.co.uk